

HISPEED MOTOR 8000

TECHNICAL DATA SHEET

September 2017

Ultra-fast motorised roll-up system with a variable speed. Easy to assemble and easy to tour. The HiSpeed Motor 8000 is compatible with all Truss Rollers, has double brakes and features smooth and accurate movement. This system, with its unique positioning control, is DMX controllable and perfect to bring drapes and screens in motion during shows. The HiSpeed Motor 8000 is compatible with RF Remote.

- Speed: 0-0.95 m/s (for Ø 10 cm Venetia Truss Roller)
0-1.45 m/s (for Ø 20 cm Truss Roller)
0-1.80 m/s (for Ø 25 cm Truss Roller)
- Capacity: 190 kg (for Ø 10 cm Venetia Truss Roller)
125 kg (for Ø 20 cm Truss Roller)
100 kg (for Ø 25 cm Truss Roller)
- Positions: full positioning control
- DMX: speed and positioning

» COMPONENTS



HiSpeed Motor 8000



Emergency Unit



Remote Unit



Power Supply Cable



Emergency Stop
Extension Cable



Emergency Stop
Link Cable



DMX Cable



Isolation Transformer

NAME	ART.NR.	WEIGHT	INFORMATION
1. HiSpeed Motor 8000	8140 3112 1017	100 kg/pc	Power: 2.2 KW • 1 x 230 V • 9 A • SWL: 190 kg Size: 40 x 40 x 100 cm
2. Emergency Unit	8140 0768 0010	2.46 kg/pc	Cable length: 25 m
3. Remote Unit	8140 0766 0010	5.75 kg/pc	Cable length: 25 m
4. Power Supply Cable	8150 0912 0027	0.40 kg/pc	Length: 2 m
5. Emergency Stop Extension Cable	8140 7202 1000 8140 7202 2500	0.87 kg/pc 2.64 kg/pc	Length: 10 m • extension cord Length: 25 m • extension cord
6. Emergency Stop Link Cable	8140 0915 0400	0.87 kg/pc	Length: 10 m
7. DMX Cable	8050 7220 5107 8050 7220 5127	0.69 kg/pc 0.85 kg/pc	Length: 10 m Length: 12.5 m
8. Isolation Transformer	8140 7260 0010 8140 7260 0040	40.40 kg/pc 70.00 kg/pc	Only transformer Transformer in flightcase