

STRETCHTULLE

TECHNICAL DATA SHEET

October 2018

Elastic mesh that stretches seamlessly up to 8 m wide. Open mesh weave for ultimate flexibility and amazing special effects. Use our flame retardant StretchTulle to create reusable fabric ceilings for your trade show booth or corporate event, or as a stretch scrim for holographic projection effects and exciting video mapping.

Mesh size: H 2 mm x W 4 mm.

» **ARTICLE CODE**

3521 0500 #

» **WIDTH**

500 cm

» **LENGTH**

± 45 m

» **WEIGHT**

200 g/m²

» **COMPOSITION**

98% PES + 2% EA

» **FLAME RESISTANCE**

NFP 92-503-507 (1980)
BS 5867 PART 2 TYPE B

CLASS M1
PASS

» **TEAR STRENGTH**

ISO 13937-3: 2000
Warp: 22N - Weft: 15N

» **TENSILE STRENGTH**

ISO 13934-1: 1999
Warp: 590N - Weft: 110N


» **AIR PERMEABILITY**

EN ISO 9237 (1995)
Average: 3980 l/(m².s)


» **COLOUR FASTNESS TO LIGHT**

ISO 105-B02-1999+Am 2002
note 6


» **AVAILABLE COLOURS**



0003



0007



0025